

3-5/6 digits 5999 Counts Dual Display Digital Multimeter

Item: MT-1820

- 3-5/6 digits 5999 counts, 0.5% best accuracy
- Dual display with analog bargraph
- Auto/Manual ranging
- USB data upload

Extra functions: duty cycle, relative reference, Max/Min hold, data hold, auto power off, low battery indication.



Specification	
DCV	600m/6/60/600V ±(0.5%+4d), 1000V ±(1.0%+6d)
ACV	6/60/600V ±(0.8%+10d), 750V ±(1.0%+10d)
DCA	600μ/6000μA ±(1.0%+10d), 60m/600mA ±(1.0%+10d), 6/10A ±(1.2%+10d)
ACA	600μ/6000μA ±(1.5%+10d), 60m/600mA ±(1.5%+10d), 6/10A ±(2.0%+15d)
Resistance	600Ω ±(0.8%+5d), 6k/60k/600k/6MΩ ±(0.8%+4d), 60MΩ ±(1.2%+10d)
Frequency	100/1000Hz ±(0.5%+4d), 10k/100kHz ±(0.5%+4d), 1M/30MHz ±(0.5%+4d)
Capacitance	40nF±(5%+30d), 400n/4μ/40μF±(3.5%+8d) 200μF±(5.0%+10d)
Temperature	-20~400°C(0~750°F) ±(1.0%+5d), 400~1000°C(750~1832°F) ±(1.5%+15d)
Continuity with buzzer	Y
Diode test	Y
Transistor test	Y
Power source	AAA(1.5V)×2pcs (Not included)
Size	7.6 x 3.7 x 1.9 in.

Order Today! SalesSupport@EclipseTools.com

Eclipse Enterprises, Inc. ● Tel: 804.561.2610 ● Fax: 804.561.2642

13302 Chula Road, Amelia Court House, VA 23002 ● EclipseTools.com