



Circular Connectors IP68
Circular Connectors AC 167 micro
AC 167 RBU/2 6-7



socket, 2 pole, voltage rating: 500 V, current rating: 10 A

Order Info

reference number (ref.no.)	72506216
PU	200
EAN	4028012130320

Type

type	socket
number of poles	2 pole
clamping units per pole	1
colour	black
coding	1 (mains)
cross-section rating	1.0 mm ²
protection against incorrect plugging	yes
latch	yes

Technical Data

voltage rating	500 V
current rating	10 A
impulse voltage rating	4.0 kV
contact material	brass
core cross-section min.	0.25 mm ²
core cross-section max.	1.0 mm ²
protection class	SK II
flammability rating	V-0
max. ambient temperature operation	60 °C
IP code	IP66/IP68/IP69
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	10.0 mm
dismantling length	20.0 mm
assembly contact screw	M2 - max. \curvearrowright 0,2 Nm

assembly strain relief	⌚ 1.5 Nm
cable diameter min.	5.8 mm
cable diameter max.	6.9 mm
strain relief	yes

Accessories

AC 167 RVKB/2 M16	729043
AC 167 RWZ/2	729044
AC 167 WKZ	729041
DR 10 1x5,5	729051
DR 10 2x2,5	729052
DR 10 3x2,5	729053