

SBS2

Touch Metal Piezo Switch



Momentary Piezo Switch

Description

Touch Metal Piezo Switch, 19mm mounting diameter, M19x1 thread, 24mm recessed actuation area. Metal housings are milled, one piece construction and mounted with a nut. Aluminum housings are available in Silver, Red, Black, Green, Gold or Blue anodization.

Approvals

- MIL-STD - 810C, 202E, 461B, 462
- CE - EVERSITCH products comply with Directives 2006/95/EEC for low voltage components.
- IP Rating – IP69K Compatible with IEC 60529; EN 60529
- EMC: Directive 2004/108/EWG

Characteristics

- Proven Reliability: Tested for 50,000,000 cycles
- Weatherproof: Used in harshest outdoor conditions
- Touch Activated: Operable with gloves, tools, etc.
- Sterilizable: Wash down proof up to 100 BAR
- Vandal Resistant: For use in high traffic and abusive areas
- Zero power required for switch operation
- Mimics a dry contact switch closure
- Eliminates RFI, EMI and ESD issues
- Five year warranty

Customized Options

A wide range of design options are available: connectors, switch function (prolonged, toggle, N.C., continuous, timer, slide and programmable types), current rating (up to 10A), graphics and housing dimensions and materials. We offer an embedded CPU for data output compatible with various communication protocols. Temperature compensated and thermal shock proof versions available as well.

References

SBS1

TECHNICAL DATA

Electrical Data

Switch Function	N.O. Momentary
Switch Voltage	0-24V AC/DC
Switch Current	0.2A std (0.5A option)
Rated Breaking Capacity	1W
Operating Cycles	>50,000,000
Switch Resistance OFF	> 5 MΩ
Switch Resistance ON	< 20 Ω
Capacity	30 pF
Pulse Duration	125-300mS
Contact Configuration	Free polarity

Mechanical Data

Housing Materials	Aluminum 6061 T651 or Stainless Steel (303/304)
Actuating Force	3-5 Newton
Connection	2x22 gauge wires
Actuating Travel	0.002 mm
Shock Protection	IK 06
Fastening Torque	2.5 Nm

Environmental Data

Operating Temperature	-40 to +125 °C
Storage Temperature	-40 to +125 °C
IP-Protection	IP69K (front and back)