



Legend™ Laser Tie-On Cable Labels

Made from durable polyester, these laser printable tie-on cable labels are designed to be printed through any ordinary office laser printer with its normal cartridge.

Use with a standard office laser printer. Removing the labels is easy too, just fold backwards and forwards along the perforation lines.

Print up to 60 labels in just 15 seconds!

Available in packs of 10 or 100 sheets.

TECHNICAL DATA

| | |
|------------------|----------------|
| Printing method: | Standard Laser |
| Material: | Polyester |
| Thickness: | 175 micron |
| Sheet Size: | A4 |
| RoHS: | Yes |
| Reach: | Yes |

Chemical/solvent resistance:

Samples of Silver Fox Legend™ laser tie-on cable labels were printed* with a standard laser printer. Samples were then conditioned for 24 hours at room temperature. Testing* consisted of 5 cycles of 10-minute immersions in the specified chemical/solvent followed by a 30-minute recovery period. After the final immersion, the samples were then rubbed ten times with a cotton swab dipped in the test fluid. Visual observations on the print quality are listed in the table to the right.

TESTING

| Test | Method |
|---------------------|---|
| Moisture Resistance | MIL-STD-202G Method 106G |
| Low Temperature | MIL-STD-810F Method 502.4 - 72 hours @ -40°C |
| High Temperature | MIL-STD-202G Method 108A - 500 hours @ 70°C |
| H2S Sour Gas | Exposure (2% H2S) |
| UV Weathering | ISO 4982 Part 3 Method A Cycle 1 - 500 hours* |
| Salt Mist Spray | IEC60068-2-52 Test Kb Salt Mist (Cyclic) |

* Limited external applications generally away from direct sunlight but may be suitable in control boxes etc. Labels generally for internal use such as, control rooms, power stations, substations etc.

| Chemical/Solvent | No Rub | After Rub |
|-------------------------------|--|--|
| Methyl Ethyl Keytone (MEK) | Loss of Density (Complete colour removal on label) | Loss of Density (Complete colour removal on label) |
| Isopropyl Alcohol | No Effect (Colour faded on label) | No Effect (Colour faded on label) |
| Toluene | No Effect (Colour faded on label) | Complete Removal |
| Jet Fuel | No Effect | Loss of Density |
| Diesel | No Effect | No Effect |
| Petrol (UK) | Loss of Density | Complete removal |
| SAE 30 Oil | No Effect | No Effect |
| De-ionised Water | No Effect | No Effect |
| 3% Alconox® Detergent | No Effect | No Effect |
| 10% Hydrochloric Acid | No Effect | No Effect |
| 10% NaCl Salt Solution | No Effect | No Effect |
| Mineral Spirits | No Effect | No Effect |
| Alcohol Mix | Complete Removal | Complete Removal |
| 10% Sodium Hydroxide Solution | No Effect | No Effect |
| DOT 4 Brake Fluid | Loss of legibility/removal | Complete removal |
| Mineralised Methylated Spirit | Complete removal | Complete removal |
| Ethylene Glycol | No Effect | No Effect |
| WD-40 | No Effect | No Effect |
| Turpentine Substitute | No Effect | No Effect |



For more information and to discuss your needs please contact our sales team on: +44 (0)1707 37 37 27 or email sales@silverfox.co.uk | www.silverfox.co.uk | support@silverfox.co.uk

Copyright © Silver Fox | 2020 Version 1



Legend™ Laser Tie-On Cable Labels

Additional Information

- Easy to use and apply
- Pre-perforated for rapid removal from sheet
- Apply to any cable from OD Ø 10mm - unlimited

APPROVALS

- Authorised for use by London Underground Registration No. 1105

ORDER INFORMATION

| Product Code | Label Dims (mm) | Labels Per Sheet | Sheets per Pack | Labels per pack | Colours* |
|--------------|-----------------|------------------|-----------------|-----------------|---------------|
| LS6013L | 60 x 13 | 60 | 10 | 600 | ○ ● |
| LM9013L | 90 x 13 | 40 | 10 | 400 | ○ ● |
| LXL9020L | 90 x 20 | 24 | 10 | 240 | ○ ● ● ● ● ● ● |

Also available in packs of 100 eg LS6013L(100)

*specify colour eg LS6013W



STORAGE INSTRUCTIONS

| | |
|----------------------|---|
| Storage Instructions | Store between 50°F (10°C) and 77°F (25°C) |
| Conditions | Keep in dark conditions |
| Humidity Resistance | 35% to 65% RH |

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice. E&OE.



For more information and to discuss your needs please contact our sales team on: +44 (0)1707 37 37 27 or email sales@silverfox.co.uk | www.silverfox.co.uk | support@silverfox.co.uk

Copyright © Silver Fox | 2020 Version 1