


L9204F

EK0506-0008 Ver.B

PIN Diode

■ FEATURES

- High power handling for VHF/UHF band
- Small capacitance at zero bias and/or extremely small reverse bias
- Low series resistance
- Very low insertion loss, high isolation
- Surface mountable plastic molded package
- RoHS compliant
- Lead free / Halogen free



size : 1.6 x 3.5 x 0.5 mm (typ)

■ MECHANICAL DATA

- Case : SOD-123 ST package molded plastic.
- Terminals : Tin plated, solderable per MIL-STD-750, method 2026.
- Polarity : Indicated by cathode band.

■ ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

SYMBOL	PARAMETER	RATING	UNITS
VR	Reverse Voltage	180	V
PD *	Power Dissipation	1	W
Tj	Junction Temperature	150	°C
Tstg	Storage Temperature Range	-55 to 150	°C

*) Mounting on glass epoxy PCB (50mm x 50mm x 1.6mm)


■ ELECTRICAL CHARACTERISTICS (Ta=25°C)

SYMBOL	PARAMETER	CONDITIONS	LIMITS			UNITS
			MIN	TYP	MAX	
IR	Reverse Current	VR = 180V	-	-	10	μA
VF	Forward Voltage	IF = 50mA	-	-	1.0	V
CT	Diode Capacitance	VR =40V, f = 100MHz	-	0.6	0.9	pF
Rfs	Forward Series Resistance	IF = 50mA, f = 100MHz	-	0.4	0.65	Ω
Rp	Parallel Resistance	VR =0V, f = 100MHz	1.0	3.0	-	kΩ

L9204F


EK0506-0008 Ver.B

MARKING INFORMATION




L6 : Parts number L9204F
 XXX : Lot Code (3~4digits)

PACKAGE OUTLINE INFORMATION







SUGGESTED PAD LAYOUT



Size	SOD-123ST
A	3.9
B1	2.3
B2	1.3
C	1.4
D	0.3
unit	mm

■ TYPICAL PERFORMANCE CHARACTERISTICS





IMPORTANT NOTICE

Litec Corporation reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.

Litec Corporation does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Litec Corporation and all the companies whose products are represented on our website, harmless against all damages.

The products located on our website at www.litec-corp.com are not recommended for use in life support systems where a failure or malfunction of the component may directly threaten life or cause injury without the expressed written approval of Litec Corporation.

CONTACT

CEL
4590 Patrick Henry Drive, Santa Clara, Ca 95054
TEL: (408) 919-2500
www.cel.com